


PRODUCT DATA SHEET



ELG6001  
MEC-FLEX QUICKFIT MECHANICS SAFETY GLOVES  
Mec-Flex Series Glove

MEC-FLEX QUICKFIT MECHANICS SAFETY GLOVES

Mec-Flex® QuickFit is a simple but effective toolbox basic. A versatile and economical glove with a multitude of uses for the professional and the handyman.

- Hyde-Tex 85 Synthetic Leather palm.
- Two-way form fitting stretch spandex on the back of the hand increasing ventilation, fit and comfort.
- Elastic easy entry cuff provides a secure fit.
- Perforated fourchettes for ventilation and increased comfort.
- Reinforced synthetic leather thumb, index, middle and ring fingertips.
- Machine washable.

PRODUCT CODE	SIZE
ELG6001MED	MEG
ELG6001LRG	LRG
ELG6001XLG	XLG
ELG60012XL	2XL

OTHER MEC-FLEX GLOVES



Mec-Flex Vibra Plus  
Anti-Vibration Glove

Mec-Flex  
Utility Gold C5 360

Mec-Flex  
Oiler Pro C5

Mec-Flex  
Rigger GT

CERTIFICATIONS & STANDARDS

These Gloves are certified by SAI Global to AS/NZS 2161.3:2005 and EN388

EN388



3121



NB2056  
CEC40027



AS/NZS  
2161.3:2005  
LN# SMK40139  
SAI GLOBAL

AS/NZS 2161.2  
EN420



General Requirements  
Risk Category  
Sizing  
Marking/labelling etc

AS/NZS 2161.3  
EN388



3121

Abrasion resistance  
Blade cut resistance  
Tear resistance  
Puncture resistance

Mechanical Hazards - Performance Levels

Test	Level 1	Level 2	Level 3	Level 4	Level 5
A: Abrasion resistance	100	500	2000	8000	-
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0
C: Tear resistance	10	25	50	75	-
D: Puncture resistance	20	60	100	150	-

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.