

PRODUCT DATA SHEET




ELG3415

G-FLEX DYNAMAX C5 ROUSTABOUT  
G-Flex Dynamax Series Glove

G-FLEX DYNAMAX C5 ROUSTABOUT

- T-Touch coating over a blue nitrile ¾ coating which offers additional layer of protection including fluids, oils and grease.
- Dynamax® C5 13 gauge seamless liner.
- Highest Cut level 5 protection.
- "Finger Dip" technology gives total ventilation to back of hand.
- Very comfortable with excellent dexterity, sensitivity and tactility.
- Good grip on most surfaces including those with light oil.
- Four sizes with colour coding identification on the cuff of each glove.

PRODUCT CODE	CUFF COLOUR	SIZE
ELG341508	Orange	8
ELG341509	White	9
ELG341510	Yellow	10
ELG341511	Brown	11



CERTIFICATIONS & STANDARDS

These Gloves are certified by SAI Global to AS/NZS 2161.3:2005 and EN388



AS/NZS 2161.2  
EN420



General Requirements  
Risk Category  
Sizing  
Marking/labelling etc

AS/NZS 2161.3  
EN388



Mechanical Hazards - Performance Levels

Test	Level 1	Level 2	Level 3	Level 4	Level 5
A: Abrasion resistance	100	500	2000	8000	-
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0
C: Tear resistance	10	25	50	75	-
D: Puncture resistance	20	60	100	150	-

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.

4543  
Abrasion resistance  
Blade cut resistance  
Tear resistance  
Puncture resistance

OTHER DYNAMAX CUT RESISTANT GLOVES

			
G-Flex Dynamax C5 AirTouch Fingerless	G-Flex Dynamax Roustabout IMPACT	G-Flex Dynamax C5 Steeler	G-Flex Dynamax C3 T-Touch Lite