

PRODUCT DATA SHEET



ELG3405

G-FLEX DYNAMAX C5 SANDSTORM

G-Flex Dynamax Series Glove

G-FLEX DYNAMAX C5 SANDSTORM


The Dynamax C5 Sandstorm has been engineered to provide a cut resistance level of 5, the highest possible cut protection.

- Lightweight "Sandy" foam nitrile coating
- Dynamax C5 Seamless liner.
- Highest Cut level 5 protection.
- "Finger Dip" technology gives total ventilation to back of hand.
- Provides highest levels of cut resistance, abrasion and tear resistance.
- Hard wearing, heavy duty glove for increased longevity
- Excellent grip on most surfaces.

MATERIALS

- Dynamax C5 liner
- Elasticated Cuff
- "Sandy" Foam Nitrile

PRODUCT CODE	CUFF COLOUR	SIZE
ELG340507	Blue	7
ELG340508	Orange	8
ELG340509	White	9
ELG340510	Yellow	10
ELG340511	Brown	11



CERTIFICATIONS & STANDARDS

These Gloves are certified by SAI Global to AS/NZS 2161.3:2005 and EN388



AS/NZS 2161.2 EN420



General Requirements
Risk Category
Sizing
Marking/labelling etc

AS/NZS 2161.3 EN388



Mechanical Hazards - Performance Levels

Test	Level 1	Level 2	Level 3	Level 4	Level 5
A: Abrasion resistance	100	500	2000	8000	-
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0
C: Tear resistance	10	25	50	75	-
D: Puncture resistance	20	60	100	150	-

Abrasion resistance
Blade cut resistance
Tear resistance
Puncture resistance

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.

OTHER DYNAMAX CUT RESISTANT GLOVES

			
G-Flex Dynamax C5 AIRTouch	G-Flex Dynamax Roustabout IMPACT	G-Flex Dynamax Roustabout	G-Flex Dynamax C3 T-Touch Lite